



SPECIFICATION OF WINTERIZED TENT



SPECIFICATION OF TENTS

4x4 Mtr, make Double Ply, four layered, center height 2.15 meter, wall height 0.90 meter, outer fold water proof, cotton canvas (uniform shade of canvas must be used) 500gsm (5%±) Inner fold water proof cotton canvas 400gsm(5%±) Polyester wadding sheet 140 gsm (5%±) for heat insulation Dyed yellow lining inner fold 130gsm (5%±), 02x door and two window (1 each side) .The winterized tents shall be fire proof.

Accessories:

3 Standing iron poles, one iron ridge pole, weight 11.50kg, iron pegs 18, pins and hammer, 8mm cotton ropes, ground sheet and plastic floor mat size 4x4 meter, weight 60-70 kg, color natural white / packing and printing of NDMA Monogram, Packing of tent and accessories in one bundle / bag wrapped in high quality canvas bag. Permanent printing of logos NDMA & Pakistan flag.



SPECIFICATION OF WINTERIZED TENT





SPECIFICATION OF WINTERIZED TENT





SPECIFICATION OF WINTERIZED TENT





SPECIFICATION OF WINTERIZED TENT





SPECIFICATION OF WINTERIZED TENT



Important Notice

- Director (Procurement) NDMA
- Ph No. 0300-2153784
- Ph No. 051-9087843
- Email: dirproc@ndma.gov.pk
- Sealed Quotations are requested on immediate basis.
- Note1: Complete price quote with applicable taxes and transportation within Pakistan is to be reflected alongwith (per day production capacity)
- Note2: The interested firms are requested to have their tent samples tested from the following labs for water and fire proofing, as follows:-
 - a. ASID Lahore - water proof test report
 - b. SGS Labs Lahore / Karachi –Fire retardant test report
- The certified samples (tested from above mentioned labs be pitched at NDMA, ERRA complex ,club road , Islamabad on immediate basis for subsequent shortlisting by the competent forum. Time for submission of both lab reports (Fire retardant from SGS and water proofing from ASID Lahore) has been extended upto 4 pm on 22.02.2023.